



**NOTE:**  
ALL RESISTANCE VALUES IN OHMS, UNLESS OTHERWISE NOTED.  
ALL VOLTAGES MEASURED TO GND. WITH "VOLTOHYST" AND WITH  
NO SIGNAL INPUT. VOLTAGES SHOULD HOLD WITHIN  $\pm 20\%$  WITH  
117V A.C. SUPPLY.

117V A.C. SUPPLY.  
BEFORE MAKING VOLTAGE MEASUREMENTS, R-10 SHOULD BE ADJUSTED SO THAT THE VOLTAGES AT PINS 1 AND 6 OF V-4 ARE EQUAL. R-60 SHOULD ALSO BE ADJUSTED SO THAT THE VOLTAGES AT PINS 1 AND 6 OF V-9 ARE EQUAL.

AT PINS 1 AND 6 OF V-9 ARE EQUAL.  
DUAL VOLTAGE READINGS SHOWN AT PINS 3 AND 5 OF V-5 WERE  
TAKEN AT THE TWO EXTREME SETTINGS OF R-35 AND R-37.

DUAL VOLTAGE READINGS SHOWN AT PINS 1, 2, AND 5 OF V-10 WERE TAKEN AT THE EXTREME SETTINGS OF R-33 AND R-37.

→ INDICATES CLOCKWISE ROTATION.

→ INDICATES CLOCKWISE ROTATION.

